



CHALLENGE

SEALER & FLOOR FINISH

CHALLENGE is a high gloss floor finish offering an outstanding balance of performance characteristics. It dries with exceptional gloss without buffing and has excellent wear properties, yet it responds beautifully to high or ultra-high speed burnishing for a deep “wet look” gloss.

CHALLENGE demonstrates excellent slip resistance and leveling as well as long-term durability. You will find it particularly outstanding in heavy traffic areas because of its superior resistance to scuffing, heel marking and dirt pickup.

CHALLENGE is:

- Durable - for longer life and higher appearance levels between maintenance operations.
- Repairable - since scratches and soils don't penetrate deeply into the polish film, less maintenance is required to restore the finish's appearance.
- “High speed maintainable” - high speed buffing is the ruin of some polishes because it is too abrasive to the surface film, but you will find that CHALLENGE stands up to high speed maintenance extremely well.
- Not “machine dependent” - it is hard and dries bright without buffing.
- Versatile - an outstanding choice for a wide variety of applications.

For best results, apply thin, even coats to a clean floor. If no seal is used, four or five coats are recommended.

TECHNICAL DATA

| | |
|--------------------|-----------------------------|
| Physical state | Liquid |
| Color | Off white, semi-translucent |
| Film color | Clear, non-yellowing |
| Odor | Mild |
| Viscosity | Free flowing |
| Storage stability | Indefinite |
| Freeze thaw cycles | 3 cycles |
| Buffability | Excellent response |

VERAX CHEMICAL COMPANY

Fax: (360) 668-5186
Phone: (360) 668-2431

20102 Broadway Ave
Maltby, WA 98296

www.veraxproducts.com
info@veraxproducts.com



| | |
|----------------------|---------------|
| Leveling | Excellent |
| Drying time (recoat) | 30-45 minutes |
| Gloss | Excellent |
| Scrubability | Excellent |
| Removability | Easy |
| Heel mark resistance | Excellent |
| Scuff resistance | Excellent |
| Hardness | Outstanding |
| Total Active | 26% |
| Floor solids | 21-22% |
| Weight per gallon | 8.6 lbs. |
| Flash point | None |
| PH | 8.2 to 8.6 |
| Coverage per gallon | 2000 sq. Ft. |

VERAX CHEMICAL COMPANY

Fax: (360) 668-5186
Phone: (360) 668-2431

20102 Broadway Ave
Maltby, WA 98296

www.veraxproducts.com
info@veraxproducts.com